Revision nr. 1 NANOPHOS S.A. Dated 28/08/2018 Printed on 28/08/2018 **SurfaGuard Metals** Page n. 1/15

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: NanoPhos GA 28082018-003

Product name SurfaGuard Metals

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Corrosion inhibitor/shop primer

1.3. Details of the supplier of the safety data sheet

NANOPHOS S.A. Name

Technological & Science Park Full address

District and Country 19 500 Lavrio (Greece)

Greece

Tel. +30 22920 69312 Fax +30 22920 69303

e-mail address of the competent person

responsible for the Safety Data Sheet iarabatz@NanoPhos.com

Product distribution by: Ioannis Arabatzis

1.4. Emergency telephone number

For urgent inquiries refer to +30 22920 69312

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Causes severe skin burns and eye damage. Skin corrosion, category 1 H314

Causes serious eye damage. Serious eye damage, category 1 H318 Hazardous to the aquatic environment, acute toxicity, H400 Very toxic to aquatic life.

Hazardous to the aquatic environment, chronic toxicity, H410 Very toxic to aquatic life with long lasting effects.

category 1

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

NANOPHOS S.A.

SurfaGuard Metals

Revision nr. 1

Dated 28/08/2018

Printed on 28/08/2018

Page n. 2/15

Hazard pictograms:





Signal words:

Danger

Hazard statements:

H314 Causes severe skin burns and eye damage. Very toxic to aquatic life with long lasting effects. H410

Precautionary statements:

P260 Do not breathe fume / gas / mist / vapours / spray.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

Immediately call a POISON CENTER / doctor. P310 Wash with plent of water thoroughly after handling. P264 P261 Avoid breathing fume / gas / mist / vapours / spray. P271 Use only outdoors or in a well-ventilated area.

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children. P103 Read label before use.

Contains: PHOSPHORIC ACID

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

PHOSPHORIC ACID

CAS 7664-38-2 10 < x < 25Skin Corr. 1B H314, Eye Dam. 1 H318, Classification note according to

Annex VI to the CLP Regulation: B

EC 231-633-2

INDEX 015-011-00-6

NANOPHOS S.A. Revision nr. 1 Dated 28/08/2018 Printed on 28/08/2018 Page n. 3/15

TRIZINC BIS (ORTHOPHOSPHATE)

CAS 7779-90-0 10 < x < 25 Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 231-944-3

INDEX 030-011-00-6

SODIUM NITRATE

CAS 7631-99-4 0 < x < 5 Ox. Sol. 3 H272, Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315,

STOT SE 3 H335

EC 231-554-3

INDEX -

PROPAN-2-OL

CAS 67-63-0 0 < x < 5 Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336

EC 200-661-7

INDEX 603-117-00-0

ETHYL SILICATE

CAS 78-10-4 0 < x < 5 Flam. Liq. 3 H226, Acute Tox. 4 H332, Eye Irrit. 2 H319, STOT SE 3 H335

EC 201-083-8

INDEX 014-005-00-0

ZINC OXIDE

CAS 1314-13-2 0,25 < x < 2,5 Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 215-222-5

INDEX 030-013-00-7

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

NANOPHOS S.A.	Revision nr. 1
	Dated 28/08/2018
SurfaGuard Metals	Printed on 28/08/2018
	Page n. 4/15

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITÄBLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire-fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

NANOPHOS S.A.	Revision nr. 1
	Dated 28/08/2018
SurfaGuard Metals	Printed on 28/08/2018
	Page n. 5/15

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

FRA

France

GBR United Kingdom JORF n°0109 du 10 mai 2012 page 8773 texte n° 102 EH40/2005 Workplace exposure limits

GRC Ελλάδα ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012 OEL EU

Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive

2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.

TLV-ACGIH **ACGIH 2018**

PHOSPHORIC ACID Threshold Limit Value	2				
Туре	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
VLEP	FRA	1	0,2	2	0,5
WEL	GBR	1		2	
TLV	GRC	1		3	
OEL	EU	1		2	
TLV-ACGIH		1		3	

PROPAN-2-OL						
Threshold Limit Value		T1444 (01		0.751 /4.5		
Туре	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
VLEP	FRA			980	400	
WEL	GBR	999	400	1250	500	
TLV	GRC	980	400	1225	500	
TLV-ACGIH		492	200	983	400	

ETHYL SILICATE						
Threshold Limit Val	ue					
Туре	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
VLEP	FRA	85	10			
TLV	GRC	170	20	255	30	
OEL	EU	44	5			
TLV-ACGIH		85	10			
Predicted no-effect cond	entration - PNEC					
Normal value in fresh wa	ater			0,192	mg/l	

NANOPHOS S.A. Revision nr. 1 Dated 28/08/2018 Printed on 28/08/2018 Page n. 6/15

Normal value in marine water	0,0192	mg/l	
Normal value for fresh water sediment	0,18	mg/kg	
Normal value for marine water sediment	0,018	mg/kg	
Normal value of STP microorganisms	4000	mg/l	

Health - Derived no-eff	fect level - DNEL / [OMEL						
	Effects on				Effects on			
	consumers				workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
				systemic		systemic		systemic
Inhalation	25 mg/m3	25 mg/m3	25 mg/m3	25 mg/m3	85 mg/m3	85 mg/m3	85 mg/m3	85 mg/m3
Skin		8.4 mg/kg bw/d		8.4 mg/kg		12,1 mg/kg		12,1 mg/kg
				bw/d		bw/d		bw/d

ZINC OXIDE					
Threshold Limit Value					
Туре	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
VLEP	FRA	5			
TLV	GRC	5		10	
TLV-ACGIH		2		10	

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear opencircuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard

NANOPHOS S.A.	Revision nr. 1
	Dated 28/08/2018
SurfaGuard Metals	Printed on 28/08/2018
	Page n. 7/15

EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

liquid

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Colour grey Odour characteristic Odour threshold Not available 1,3 Melting point / freezing point Not available Not available Initial boiling point Not available Boiling range > 100 °C Flash point Evaporation rate Not available Flammability (solid, gas) Not available Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit Not available Upper explosive limit Not available Vapour pressure Not available Vapour density Not available Relative density 1.23±0.05 kg/L Solubility Not available Partition coefficient: n-octanol/water Not available Auto-ignition temperature Not available Not available Decomposition temperature Viscosity 2 mPa.s Explosive properties Not available Oxidising properties Not available

9.2. Other information

VOC (Directive 2010/75/EC): 0,37

SECTION 10. Stability and reactivity

10.1. Reactivity

Appearance

PHOSPHORIC ACID

Decomposes at temperatures above 200°C/392°F.

10.2. Chemical stability

Information not available

10.3. Possibility of hazardous reactions

The product may react violently with water.

NANOPHOS S.A.	Revision nr. 1
	Dated 28/08/2018
SurfaGuard Metals	Printed on 28/08/2018
	Page n. 8/15

PHOSPHORIC ACID

Risk of explosion on contact with: nitromethane. May react dangerously with: alkalis, sodium borohydride.

10.4. Conditions to avoid

Avoid overheating. Prevent moisture or water from penetrating inside the containers.

10.5. Incompatible materials

PHOSPHORIC ACID

Incompatible with: metals, strong alkalis, aldehydes, organic sulphides, peroxides.

10.6. Hazardous decomposition products

PHOSPHORIC ACID

May develop: phosphoryl oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture: > 20 mg/l LD50 (Oral) of the mixture: >2000 mg/kg

NANOPHOS S.A. Revision nr. 1 Dated 28/08/2018 Printed on 28/08/2018 Page n. 9/15

LD50 (Dermal) of the mixture: Not classified (no significant component)

ETHYL SILICATE

LD50 (Oral) 2,5 mg/kg

LD50 (Dermal) 5878 mg/kg RABBIT

LC50 (Inhalation) 11 mg/l/4h

PHOSPHORIC ACID

LD50 (Oral) 1530 mg/kg Rat

LD50 (Dermal) 2740 mg/kg Rabbit

LC50 (Inhalation) > 0,85 mg/l/1h Rat

PROPAN-2-OL

LD50 (Oral) 4710 mg/kg Rat

LD50 (Dermal) 12800 mg/kg Rat

LC50 (Inhalation) 72,6 mg/l/4h Rat

TRIZINC BIS (ORTHOPHOSPHATE)

LD50 (Oral) > 5000 mg/kg Rat - Wistar

LC50 (Inhalation) > 5,7 mg/l Rat

SODIUM NITRATE

LD50 (Oral) 1267 mg/kg Rat

SKIN CORROSION / IRRITATION

Corrosive for the skin

Classification according to the experimental Ph value

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

NANOPHOS S.A. Revision nr. 1 Dated 28/08/2018 Printed on 28/08/2018 Page n. 10/15

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

This product is dangerous for the environment and highly toxic for aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

ETHYL SILICATE

 LC50 - for Fish
 > 245 mg/l/96h

 EC50 - for Crustacea
 > 75 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 > 100 mg/l/72h

TRIZINC BIS (ORTHOPHOSPHATE)

LC50 - for Fish 0,78 mg/l/96h Pimephales promelas EC50 - for Crustacea 0,86 mg/l/48h Daphnia magna

Chronic NOEC for Algae / Aquatic Plants 5,2 mg/l

ZINC OXIDE

LC50 - for Fish 1,1 mg/l/96h Oncorhynchus mykiss EC50 - for Crustacea 1,7 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants 0,14 mg/l/72h Pseudokirchnerella subcapitata

Chronic NOEC for Fish 0,53 mg/l
Chronic NOEC for Algae / Aquatic Plants 0,024 mg/l

NANOPHOS S.A. Revision nr. 1 Dated 28/08/2018 Printed on 28/08/2018 Page n. 11/15

12.2. Persistence and degradability

ETHYL SILICATE

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

PHOSPHORIC ACID

Solubility in water > 850000 mg/l

Degradability: information not available

PROPAN-2-OL Rapidly degradable

TRIZINC BIS (ORTHOPHOSPHATE)

Solubility in water 2,7 mg/l

Degradability: information not available

SODIUM NITRATE

Solubility in water > 10000 mg/l

Degradability: information not available

ZINC OXIDE

Solubility in water 2,9 mg/l
Solubility in water 0,1 - 100 mg/l

Degradability: information not available

NOT rapidly degradable

12.3. Bioaccumulative potential

ETHYL SILICATE

Partition coefficient: n-octanol/water 3,18 BCF 3,16

PROPAN-2-OL

Partition coefficient: n-octanol/water 0,05

ZINC OXIDE

BCF > 175

12.4. Mobility in soil

Information not available

NANOPHOS S.A.	Revision nr. 1
	Dated 28/08/2018
SurfaGuard Metals	Printed on 28/08/2018
	Page n. 12/15

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, 3264

IATA:

14.2. UN proper shipping name

ADR / RID: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (PHOSPHORIC ACID)

IMDG: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (PHOSPHORIC ACID; TRIZINC BIS (ORTHOPHOSPHATE))

IATA: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (PHOSPHORIC ACID)

14.3. Transport hazard class(es)

ADR / RID: Class: 8 Label: 8

IMDG: Class: 8 Label: 8

IATA: Class: 8 Label: 8



14.4. Packing group

ADR / RID, IMDG, II

IATA:

Revision nr. 1 NANOPHOS S.A. Dated 28/08/2018 Printed on 28/08/2018 SurfaGuard Metals Page n. 13/15

14.5. Environmental hazards

ADR / RID: Environmentally

Hazardous

IMDG: Marine Pollutant

IATA: NO

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

Pass.:

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 80 Limited Tunnel Quantities: 1 restriction

code: (E)

IMDG: EMS: F-A, S-B Limited

Special Provision: -

Quantities: 1

Maximum

IATA: Cargo: quantity: 30 L

instructions: 855

Packaging

Maximum Packaging

quantity: 1 L instructions: 851

Special Instructions: A3, A803

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: E1

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>

3 Point

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

NANOPHOS S.A.	Revision nr. 1
	Dated 28/08/2018
SurfaGuard Metals	Printed on 28/08/2018
	Page n. 14/15

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2 Flammable liquid, category 2
Flam. Liq. 3 Flammable liquid, category 3
Ox. Sol. 3 Oxidising solid, category 3
Acute Tox. 4 Acute toxicity, category 4
Skin Corr. 1B Skin corrosion, category 1
Skin Corr. 1 Scrious eye damage, category 1

Eye Irrit. 2 Eye irritation, category 2
Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1

Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H272 May intensify fire; oxidiser.
H302 Harmful if swallowed.
H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H315 Causes skin irritation.

H335 May cause respiratory irritation.H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Revision nr. 1 NANOPHOS S.A. Dated 28/08/2018 Printed on 28/08/2018 SurfaGuard Metals Page n. 15/15

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a quarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.